




INSTALLATION AND OWNER'S MANUAL
Carbon Fiber Gauge Panel Trim Kits: Z8600, Z8601,
Z8602, Z8603, Z8604, Z8640, Z8641 and Z8611

CARBON FIBER KIT CONTENTS:

Part No.	Description	Qty.
Z8600 Kit	Gauge Panel Trim Alcohol Wipe	2 piece 1 piece
Z8601 Kit	Gauge Panel Trim Alcohol Wipe	2 piece 1 piece
Z8602 Kit	Gauge Panel Trim Alcohol Wipe	4 piece 1 piece
Z8603 Kit	Gauge Panel Trim Alcohol Wipe	3 piece 1 piece
Z8604 Kit	Gauge Panel Trim Alcohol Wipe	6 piece 2 piece
Z8640 Kit	Gauge Panel Trim Alcohol Wipe	2 piece 1 piece
Z8641 Kit	Gauge Panel Trim Alcohol Wipe	2 piece 1 piece
Z8611 Kit	Gauge Panel Trim Alcohol Wipe	1 piece 1 piece



Hand Held Hair Dryer, 1500 Watt
 Mild Soap and Water for Cleaning
 Tweezers
 Soft Cloth

PREPARATION

1. Thoroughly clean the motorcycle's dash panel surface around the gauges and warning lights. First wash the dash area, as you would normally clean the motorcycle.

2. After drying with the paper towels, clean again with the alcohol wipes. Do not apply wax or polish to the area cleaned.

INSTALLATION

1. Test fit the carbon fiber pieces on the dash to verify their location. Do this before removing any adhesive mask.

2. Warm the dash panel to about 100° F (37° C) (hair dryer).

3. Warm the carbon fiber covers to 100° F (37° C) (hair dryer).

4. When everything is warm, carefully remove the masking from the adhesive side of the carbon fiber dash panel, one piece at a time (tweezers).

5. Position the carbon fiber dash panel pieces on the dash panel so it fits around the gauges and does not cover any warning lights.

6. If it is necessary to reposition any piece, warm the piece and slowly peel it from the surface. Be careful not to stretch or over bend the piece.

7. Once the pieces are correctly positioned, firmly, but carefully, press the carbon fiber dash panel onto the warm dash panel.

8. Once properly positioned, and still warm, carefully use the soft cloth to rub the carbon fiber dash panel onto the dash panel until it is completely adhered.

9. After 24 hours, the adhesive on the carbon fiber dash panel will have set completely.

CAUTION

1. Do not use heat guns or open flame to warm the pieces or the motorcycle, they produce too much heat and may create a fire hazard.

2. Warming temperature is critical for the best performance and adhesion. Installing a warm piece onto a cold surface is not recommended.

3. Cleaning is critical. Be sure to remove all wax, cleaners, and protectants (Armor-All). These can foul the adhesive causing it to fail.

MAINTENANCE

Clean and polish the carbon fiber dash panel with Turtle Wax® vinyl fabric upholstery cleaner and protector. Spray wax or cleaner on cloth and wipe the carbon fiber covers. Never apply waxes or cleaners directly to the carbon fiber covers.

